



Manfrotto

bogen
imaging

501HDV-351MVB KIT

Designed to accommodate evolving **Video** technology, the 501HDV features improved drag in both axes and switchable counterbalance for the latest Ultra Light **High-Definition** Camcorders. In addition, controls have been repositioned and reshaped for superior operational ergonomics. A sliding camera plate helps balance uneven payloads due to outboard **Batteries** or matte boxes, dual rosettes permit left- or two-handed pan arm configurations, and the rear-mounted spirit level facilitates rapid setups. Simplicity and strength are the two main features of the 1-stage aluminum alloy 351MVB tripod. One stage means longer leg tubes with fewer joints, and therefore a more rigid support. Designed with tandem upper legs and single lower legs with variable angle adjustment and twin-spiked feet, the 351MVB Tripod is supplied with a 75 mm half-bowl attachment. A built-in spreader is achieved with the two-step leg angle positioning system located at the top tripod spider.

- **Includes: 501HDV Fluid Head, 351MVB Tripod,**
- Fixed counterbalance optimized for 5.5 pounds (2.5 kg) payloads
- Fixed fluid drag enhanced with Teflon friction assist
- Sliding camera plate for uneven camera/lens payloads
- Dual pan arm rosettes for left or two-handed configurations
- Mid-level spreader folds into legs for convenient transport
- Tripod Maximum Height: 24 to 67.1-inch (61 cm to 170.4 cm)
- Tripod Folded Length: 40.7-inch (103.4 cm)
- Load Capacity: 13.2 pounds (6.0 kg)
- Tripod Weight: 12.5 pounds (5.6 kg)
- Counter Balance System Fixed spring



- Balance Plate with 58mm of travel
- 1-Step Pan & Tilt Drag
- -60 to +90 Degrees Tilt Range
- 360 degrees Pan Range
- Separate & Pan Tilt Lock
- Aluminum Alloy Head Material
- Head Attachment: Fitting 3/8-16
- Head to Leg Lock Type: Fast-action clamps
- Center Brace Mid-level Head
- Head Closed length: 93.00 cm
- Head Height: 84.0 cm to 151.0 cm
- Weight Capacity: 20.00 kg
- Head Weight: 3.60 kg

